



**EXIDE**  
BATTERY CHARGER

# 12/2 Li-Ion

## Operating Manual



### OPERATING INSTRUCTIONS

- › Make sure the charger's input voltage matches the AC voltage
- › Plug the charger to the power supply. The LED light should turn green
- › Connect the red clamp to the battery's positive terminal and the black clamp to the negative terminal. The LED light turns red indicating the start of charging
- › The LED light becomes green when the battery is fully charged

### FEATURES & FUNCTIONS

- › Maximum safety: No current or voltage when the charger is not connected to the battery
- › Maintenance charge: The charger can be used to perform maintenance charge when the vehicle is in storage or used infrequently
- › Automatic verification: The charger stops charging if the battery voltage cannot reach 10V after two hours
- › Low voltage recovery: When the battery voltage drops below 8V, the charger will perform a recovery charge with 0.2Amps until the voltage reaches 8V. Then the current will automatically switch to 0.5Amps to continue charging until the voltage reaches 10V
- › Constant charge current: when the battery voltage is over 10V, the charger will deliver a constant current of 2Amps until the battery voltage reaches the limit of 14.2V
- › Floating charge: The charger switches to floating charge mode and gradually reduces current when battery voltage reaches 14.2V

### LED LIGHT STATUS

- › Green when not connected to the battery: the charger is connected to the power supply
- › Green when connected to the battery: the battery is fully charged
- › Red light: battery voltage is between 8.0V to 14.2V
- › Red flashing light: the battery voltage is less than 8V; or there is short circuit; or clamps are not correctly connected to the battery terminals

### TECHNICAL SPECIFICATION

Battery capacity	Up to 360Wh
AC input voltage	100 - 240V 50/60Hz
Output voltage	14.2V ± 0.2A
Output current	2A ± 0.1A
Short-circuit protection	Yes
Polarity reverse protection	Yes
Over charge protection	Yes
Operating temperature	-10°C to 40°C
Storage temperature	-40°C to 70°C
Operating humidity	5% - 95%RH
Certificates	<b>CE RoHS</b>

### CAUTION

- › Do not expose to rain - indoor use only
- › Keep away from explosive gas or sparks
- › Do not cover the charger during use
- › Switch off the power supply before removing the charger from the battery
- › Keep away from children

Scan to read the manual in other languages:

[www.exide.info/motorbike](http://www.exide.info/motorbike)



**EXIDE**  
BATTERIES

**Li-Ion**

Motorbike & Sport Battery

[www.exide.info/motorbike-liion](http://www.exide.info/motorbike-liion)  
PRODUCT INFORMATION

Exide Technologies  
Original Equipment Manufacturer



1 - 360Wh

**EXIDE 12V/2A Li-Ion**

1 - 360Wh